

ARTISTE
SERIES

PAINT YOUR VISION



ARTISTE
MONDRIAN

ARTISTE
MONET

ARTISTE
VAN GOGH

ARTISTE
REMBRANDT

ARTISTE
PICASSO



ARTISTE
SERIES

Optional
PC Lens

ARTISTE
DaVINCI



WINNER OF THE
plasa 2019
AWARDS FOR INNOVATION

WORSHIP FACILITIES
NEW PRODUCT AWARDS 2017

WORSHIP FACILITIES
NEW PRODUCT AWARDS 2018

READERS' CHOICE AWARDS 2018
ProSoundWeb & Live Social International
WINNER



CREATIVE DESIGN

Built to make the design task easier while empowering designers to create truly unique works of art, these inspirational theatrical-grade spot, profile and wash luminaires with white LED engines offer a complete palette for the creative designer in an energy-efficient design.




CONSISTENT COLOR

With color choice perhaps the central element in mood generation, these innovative luminaires offer full CMY or CMYRGB SpectraColor color mixing systems capable of producing a full spectrum of shades from delicate pastels to rich saturates. Linear CTO color correction has been included for more refined color temperature control and a wider range of color capabilities. State-of-the-art optical designs combine with highly efficient LED engines and tight LED binning to produce a consistent light quality and overall superior projections.



ENDLESS FRAMING

The ability to manipulate the shape of the beam is vital in professional lighting, especially theatrical environments. An unlimited indexing and continuous rotation framing system allows users to not only refine the beam shape and frame around objects to be highlighted, but allows for creative transitions, projections, reveals and aerial effects when used in combination with the 4 full-blackout framing blades.



With greater possibilities comes greater creative freedom and with the Artiste Series the artistic door has been swung wide open. Designers all over the world are discovering that these multi-award-winning theatrical grade luminaires are as creative as the artistic icons they are named after. Artiste has set a new benchmark for creative expression in automated LED moving heads.



FEATURE PACKED

The Mondrian, Monet and Rembrandt come loaded with state-of-the-art FX packages to complement any show setting. The DaVinci and Picasso are loaded with features and graphic design options like zoom, gobos, animation, added colors and prisms while the Van Gogh framing wash luminaire makes for their ideal partner with its included Fresnel or PC lens options.

SpectraColor

Thanks to Elation's exclusive SpectraColor color mixing, the Artiste Monet, Mondrian and Rembrandt are capable of projecting some of the most gorgeous colors ever produced by an automated LED luminaire. SpectraColor combines industry standard CMY with complementary RGB flags for the ability to fade between soft pastels to deep saturated primary colors. With the addition of variable CTO, as well as a static color wheel to cover specific shades, these creative luminaires can produce the color combinations that lighting designers require.



SUPERIOR OPTICS

LED light engines that are custom designed for efficient optical systems provide maximum performance and greater consistency in projection. Whether you require a uniform, flat field of refined light, or a powerful hotspot for long distances, the Artiste series has the solution for you. Additional glass gobo image projections and customized animation effects provide limitless texture and layering solutions for the largest and most demanding applications.

Product Overview



SOURCE

- 620W, Profile, 6,800K Cool White LED Engine
- 30,000 Hour Average LED Life*

SOURCE

- 380W, Wash, 6,500K Bright White LED Engine
- 20,000 Hour Average LED Life*

SOURCE

- 950W, Profile FX, 6,500K Bright White LED Engine
- 30,000 Hour Average LED Life*

SOURCE

- 950W, Profile, 6,500K Bright White LED Engine
- 30,000 Hour Average LED Life*

SOURCE

- 950W, Wash, 6,500K Bright White LED Engine
- 30,000 Hour Average LED Life*

SOURCE

- 270W, Spot, 7,000K Cool White LED engine
- 50,000 Hour Average LED Life*

PHOTOMETRIC DATA

- 23,000 Total Lumen Output
- CRI 73+ (87+ with HCRI Filter)

PHOTOMETRIC DATA

- 16,000 Total Lumen Output
- CRI 91

PHOTOMETRIC DATA

- 51,000 Total Lumen Output
- CRI 72+ (84+ with HCRI Filter)

PHOTOMETRIC DATA

- 45,000 Total Lumen Output
- CRI 72+ (84+ with HCRI Filter)

PHOTOMETRIC DATA

- 51,000 Total Lumen Output
- CRI 72+ (82+ with HCRI Filter)

PHOTOMETRIC DATA

- 12,000 Total Lumen Output
- CRI 72+

EFFECTS

- 7°-55° Motorized Zoom
- 4 Rotating Full Blackout Framing Blades
- Full 360° bi-directional Animation Wheel
- 4-Facet and Linear Rotating Prisms
- 2 Frost Filters
- Internal Color, Framing, Prism, and Frost Macros
- Motorized Iris with Variable Pulse Effects
- Variable 16-bit Dimming Curve Modes
- High Speed Electronic Shutter and Strobe
- Adjustable LED Refresh Rate Frequency and Gamma

EFFECTS

- 7.5°-45° Beam Zoom Angle (PC Lens Included)
- 11°-66° Beam Zoom Angle (Fresnel Lens included)
- CMY+ CTO Color Mixing
- 7 Position Fixed Color Wheel including UV
- 4 Independent Barn Doors
- Barn Door Index Adjustment
- Frost Filter
- Remote Focus Adjustment
- Electronic Strobe and Variable Dimming Curves
- 16-bit Dimming

EFFECTS

- 3°-45° Motorized Zoom (226mm / 8 3/4" Front Lens)
- 4 Rotating Full Blackout Framing Blades
- 360° Continuous Framing Index and Rotation
- Full 360° bi-directional Animation Wheel
- 2 Rotating Prisms
- 2 Variable Frost Filters (Light and Wash)
- Internal Color, Framing, Prism, and Frost Macros
- Motorized Iris with Variable Pulse Effects
- Variable 16-bit Dimming Curve Modes

EFFECTS

- 6.8°-55° Motorized Zoom (160mm Front Lens)
- 4 Rotating Full Blackout Framing Blades
- 360° Continuous Framing Index and Rotation
- Full 360° bi-directional Animation Wheel
- 4-facet and Linear Rotating Prisms
- 2 Variable Frost Filters (Light and Wash)
- Internal Color, Framing, Prism, and Frost Macros
- Motorized Iris with Variable Pulse Effects
- Variable 16-bit Dimming Curve Modes

EFFECTS

- 8°-50° Motorized Zoom (180mm Front Lens)
- 4 Full Blackout Framing Blades
- 360° Framing Index - Continuous Framing Rotation
- 2 bi-directional Animation Wheels
- 2 Variable Frost Filters (Medium, Heavy)
- High Speed Iris
- Focus Edge Control
- Variable 16-bit Dimming Curve Modes
- High Speed Electronic Shutter and Strobe
- Adjustable LED Refresh Rate Frequency

EFFECTS

- 6°-48° Motorized Zoom
- 3-Facet and Linear Rotating Prisms and Prism Macros
- Full 360° bi-directional Rotating Animation Wheel
- Frost Filter Hybrid Wash Effect
- Motorized Zoom, Iris, Focus and Auto-Focus
- High Speed Electronic Shutter and Strobe
- Variable 16-Bit Dimming Curve Modes
- Adjustable LED Refresh Rate Frequency and Gamma Brightness

COLOR

- Full CMY Color Mixing System
- Linear CTO Color Correction
- 6 Dichroic Colors including High 87 CRI Filter

COLOR

- Full CMY Color Mixing System
- Linear CTO Color Correction
- 7 Dichroic Colors including UV

COLOR

- SpectraColor CMY + RGB Color Mixing Array
- Linear CTO Color Correction
- 6 Dichroic Colors including High CRI + UV

COLOR

- SpectraColor CMY + RGB Color Mixing Array
- Linear CTO Color Correction
- 6 Dichroic Colors including High CRI + UV

COLOR

- SpectraColor CMY + RGB Color Mixing Array
- Linear CTO Color Correction
- 6 Dichroic Colors including High CRI + UV

COLOR

- Full CMY Color Mixing
- 7 Dichroic Colors + CTB
- Linear CTO Color Correction

GOBOS

- 2 Gobo Wheels
- 7 Rotating / Indexing Interchangeable Glass
- 7 Interchangeable Static-Stamped Metal Gobos

GOBOS

- N/A

GOBOS

- 2 Gobo Wheels
- 12 Rotating / Indexing Interchangeable Glass Gobos

GOBOS

- 2 Gobo Wheels
- 7 Rotating / Indexing Interchangeable Glass Gobos
- 7 Static Interchangeable Glass Gobos

GOBOS

- N/A

GOBOS

- 2 Gobo Wheels
- 6 Rotating / Indexing Interchangeable
- 9 Static Interchangeable Metal Gobos

CONTROL / CONNECTIONS

- 2 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- Motorized Focus and 5-15m Auto-Focus presets
- DMX, RDM, Art-NET, and sACN Protocol Support
- Elation's E-FLY™ Internal Wireless DMX Transceiver
- 6 Button Touch Panel
- Full Color 180° Reversible LCD Menu Display
- 8 / 16 Bit Resolution Adjustable Movement
- Hibernation Mode
- Locking 5pin XLR In/Out
- Locking RJ45 Ethernet In/Out
- Locking Power In/Out

CONTROL / CONNECTIONS

- 2 DMX Channel Modes (22 / 36 Channels)
- DMX Adjustable Refresh Rate (900 -25,000 Hz)
- 6 Button Touch Panel
- Full Color 180° Reversible LCD Menu Display
- DMX, RDM, Art-NET, and sACN Protocol Support
- Locking 5pin XLR In/Out
- Locking RJ45 Ethernet In/Out
- Locking Power In/Out

CONTROL / CONNECTIONS

- 2 DMX Channel Modes (42 / 68)
- 16-bit Pan, Tilt and Dimming Control
- Motorized Focus and Auto-Focus Presets
- DMX, RDM, Art-NET, and sACN Protocol Support
- 6 Button Touch Control Panel
- Full Color 180° Reversible LCD Menu Display
- Hibernation Mode
- Locking 5pin XLR In/Out
- Locking RJ45 Ethernet In/Out
- Locking Power In

CONTROL / CONNECTIONS

- 2 DMX Channel Modes (40 / 67)
- 16-bit Pan, Tilt and Dimming Control
- Motorized Focus and Auto-Focus Presets
- DMX Controllable Variable Fan Modes
- DMX, RDM, Art-NET, and sACN Protocol Support
- 6 Button Touch Control Panel
- Full Color 180° Reversible LCD Menu Display
- Hibernation Mode
- Locking 5pin XLR In/Out
- Locking RJ45 Ethernet In/Out
- Locking Power In

CONTROL / CONNECTIONS

- 2 DMX Channel Modes
- 16-bit Pan, Tilt, and Dimming Control
- DMX, RDM, Art-NET, and sACN Protocol Support
- 6 Button Touch Control Panel
- Full Color 180° Reversible LCD Menu Display
- Hibernation Mode
- Locking 5pin XLR In/Out
- Locking RJ45 Ethernet In/Out
- Locking Power In

CONTROL / CONNECTIONS

- 3 DMX Channel Modes (40 Total Channels)
- 6 Button Touch Control Panel
- Full Color 180° Reversible LCD Menu Display
- 8 / 16 Bit Resolution Adjustable Movement
- Elation's E-FLY™ Internal Wireless DMX Transceiver
- DMX, RDM, Art-NET, and sACN Protocol Support
- Locking 5pin XLR In/Out
- Locking RJ45 Ethernet In/Out
- Locking Power In/Out

SIZE / WEIGHT

- LxWxH: 457 x 544.5 x 757.5 mm (18.0" x 21.5" x 29.8")
- Weight: 38.1 kg (84.0 lbs.)

SIZE / WEIGHT

- LxWxH: 399.6 x 447.3 x 669 mm (15.7" x 17.6" x 26.3")
- Weight: 28.5 kg (62.8 lbs.)

SIZE / WEIGHT

- LxWxH: 673 x 472 x 870 mm (26.5" x 18.5" x 34.2")
- Weight: 47.5 kg (104.7 lbs.)

SIZE / WEIGHT

- LxWxH: 471.1 x 583.4 x 800.4 mm (18.6" x 22.9" x 31.5" in)
- Weight: 42.6 kg (94.0 lbs.)

SIZE / WEIGHT

- LxWxH: 471 x 333 x 805 mm (18.5" x 31.1" x 31.7" in)
- Height (optional PC Lens) 793 mm (31.2")
- Weight: 43 kg (94.7lbs.)

SIZE / WEIGHT

- LxWxH: 416 x 284 x 645 mm (16.4" x 11.2" x 25.4" in)
- Weight: 25.4 kg (56.0 lbs.)



Elation Professional Europe
 Junostraat 2 • 6468 EW Kerkrade • The Netherlands
www.elationlighting.eu

*Lamp/ LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming. Gobos & Colors. Specifications subject to change without notice.